

Introduction:

Material is defined as that which consists of matter or occupies space. The common uses of material are in food particles, medicines, house, clothes, transportation and many more. Engineers and technologists need different materials for design and manufacturing of aircrafts, engines, ship building, construction etc. Materials are an essential part of engineering industry. An engineer needs materials to give shape for his concepts and design.

Classification:

Engineering materials may be classified into 4 broad types based on their nature.

- (i) Metals and alloys
- (ii) Ceramics
- (iii) Polymers
- (iv) Composites

Metal is an elemental substance in pure form while an alloy is formed when two or more metal are mixed together to form a homogenous mixture. Metals can be either **ferrous** or **non-ferrous**. Ferrous metals contain iron while non-ferrous metals do not. Both ferrous and non-ferrous metals are divided into pure metals and alloys. Ex: Iron and steel. An alloy is a mixture of two or more elements (Ex: iron and carbon) to make another metal with particular properties (Ex: steel).

Ceramics are compounds of metallic and non-metallic elements which are very hard in nature. Ex: Silicon carbide and magnesium oxide

Polymers are direct derivatives of carbon while are having long chain molecules with 3D structures. Ex: Plastics and polyethylene

Composites are special materials where, one or more reinforcements are added the base metal (matrix) to form a heterogeneous mixture. Here the properties of the base metal are enhanced by adding small quantity of reinforcing materials. Ex: Fibre reinforced plastics (FRP) and carbon reinforced rubber.

Metals


A metal is a material that is typically hard, opaque, shiny, and features good electrical and thermal conductivity. Metals are generally malleable: they can be hammered or pressed permanently out of shape without breaking or cracking well as fusible and ductile.

Metals can be either ferrous or non-ferrous. Ferrous metals contain iron while nonferrous metals do not. Both ferrous and non-ferrous metals are divided into pure metals and alloys.

A pure metal is an element – Ex: iron, copper, gold - unalloyed (not mixed) with another substance.

An alloy is a mixture of two or more elements (Ex: iron and carbon) to make another metal with Particular properties (Ex: steel).

CLASSIFICATION




Ferrous metals:

Ferrous metals contain iron. Examples are cast iron, mild steel, medium carbon steel, high carbon steel, stainless steel, and high speed steel.

Types of ferrous Metals:

STEEL

Steel is an alloy of iron and iron carbide in which the maximum percentage of carbon is 1.5%. The difference between cast iron and steel is the percentage of carbon present. Higher the percentage of this carbon, harder and tougher is the steel. Carbon content cannot be increased in the metal in chemically combined form beyond 1.5 percent. If this proportion is increased beyond this limits it moves the metal into the category of cast iron. Thus, steel can be said to be an alloy of iron and carbon with the carbon content to a maximum of 1.5 percent. These steels are called plain carbon steels because they owe their properties mainly to the percentage of carbon present in them. These steels are classified into different groups as follows:



a) Carbon steels: carbon steels are types of steel containing primarily iron and carbon. Other elements present in small proportions are sulphur, phosphorous, manganese and magnesium. The following types of carbon steel are.

i) Mild steel or Low carbon steel

Composition: It has a carbon content of 0.05 to 0.3%. The balance is iron. The most popularly used carbon steel is mild steel.

Properties and characteristics: Tough, ductile and malleable. Good tensile strength, poor resistance to corrosion.

Application: General-purpose engineering material like rivets, bolts, keys plain washer boiler plate's shaft, camshafts and gear.

ii) Medium carbon steel

Composition: It has a carbon content of 0.3 - 0.6% carbon. The remainder is iron content.

Properties and characteristics: Strong, hard and tough, with a high tensile strength, but less ductile than mild steel.

Application: It finds application in transmission shafts, springs, spring washers, crane hooks and hand tools etc.

iii) High carbon steel

Composition: It has a carbon content of 0.6 - 1.5%. it has an iron content of 96% to 97%.

Properties and characteristics: Even harder than medium carbon steel, and more brittle. Can be heat treated to make it harder and tougher.

Application: Cutting tools, hammers, chisels, screw, punches, drills lathe tools, leaf springs and milling cutter.

Alloy Steels

Plain carbon steel possess very poor strength, corrosion resistance and fatigue resistance. Alloy steels are obtained by adding some elements as nickel, chromium, cobalt, vanadium, tungsten, silicon etc., to the carbon steel to get the desired properties. Alloy steels are developed to accomplish one or more of the following :-

1. To improve tensile strength, elastic limit and ductility.
2. To provide free cutting properties (lead is added to steel).
3. To improve wear and corrosion resistance.
4. To improve machinability and weldability.
5. To refine the grain structure of steel.

Some of the important alloy steels are discussed below :-

Stainless steel

Composition: Alloy of iron and carbon with 16-26% chromium, 8-22% nickel and 8% magnesium

Characteristics: Hard and tough, resists wear and corrosion.

Application: Cutlery, kitchen equipment, surgical equipment, chemical handling equipments and cutler etc.


High speed steel

Composition: Alloy of iron and 0.8 - 1.2% carbon (medium carbon steel) with tungsten, chromium, vanadium, and sometimes cobalt.

Properties and characteristics: Very hard, high abrasion- and heat resistance

Application: Cutting tools for machines.

TYPES OF CAST IRON



1. Grey Cast Iron. This type of cast iron is obtained by allowing the molten metal to cool and solidify slowly. Grey cast iron contains 2.5 to 3.75% of carbon.

Properties

1. Grey cast iron is brittle and may be broken if a heavy hammer is used.
2. Melting point is low.
3. It is easily machinable.
4. The graphite present, acts as a lubricant.

Applications

1. Machine tool structure.
2. Gas or water pipes for underground purposes.
3. Cylinder blocks and heads for I.C. Engines.
4. Frames for electric motors.

2. White Cast Iron. It contains 1.75% to 2.3% carbon.

Properties

1. White cast iron is very hard and brittle,
2. It is wear resistant and less ductile.
3. It can not be machined.

Applications

1. Used for manufacturing wrought iron,
2. For manufacturing those component parts which require a hard and abrasion resistant material.
3. For producing malleable iron casting.

3. Malleable Cast Iron. Malleable cast iron is obtained from white cast iron by special annealing process. This type of cast iron contains 2 to 3.6% carbon.

Properties

1. It is less brittle.
2. Tensile strength of malleable cast iron is 180 N/mm^2 .
3. Good wear resistance and vibration damping capacity.

Applications

1. Automobile parts.
2. Sewing machine parts.
3. Bicycle parts.
4. Agricultural equipments.
5. Electrical line hardware.
6. Universal joint yoke.
7. Conveyor chain links.
8. Suitable for small and medium size castings of high strength.

4. Ductile Cast Iron. It is also called spheroidal cast iron because the graphite is precipitated not in the form of flakes but in the form of spheroids. This is high grade cast iron. It is also called ductile cast iron.

Properties

1. It has very good casting properties as high fluidity and low melting point.
2. It produces better machined surfaces.
3. The tensile strength is 330 N/mm^2 .
4. High strength and toughness.
5. Good resistance to wear.
6. Higher machinability than grey cast iron.
7. It can be welded nicely.
8. The value of modulus of elasticity is high.

Applications

1. Paper industries machinery.
2. Internal combustion engines.
3. Power transmission equipment.
4. Farm implements and tractors.
5. Earth moving machinery.

Non-ferrous metals

Non-ferrous metals do not contain iron. Some common non-ferrous metals are aluminum, copper, zinc, tin, brass (copper + zinc), and bronze (copper + tin).

PHYSICAL AND MECHANICAL PROPERTIES OF NON-FERROUS METALS AND THEIR APPLICATIONS

<i>S.No.</i>	<i>Metals</i>	<i>Properties</i>	<i>Applications</i>
1.	Aluminium	1. Ductile and malleable. 2. Silvery white colour. 3. Melting point is 659.8°C.	1. Electrical wires and cables. 2. Automobile parts and bodies. 3. Aluminium sheets are used for stamping. 4. Kitchen utensils. 5. Furniture. 6. Piston of automobile engines. 7. Aluminium paint is used as protective coating.

2.	Copper	1. Very good conductor of heat and electricity. 2. Reddish brown in colour. 3. Good weldability and machinability. 4. Melting point is 1084°C.	1. Largely used for electric wires. 2. Used in condensers, evaporators where heat transfer takes place. 3. Used for electroplating. 4. Radiator fins. 5. Boiler parts.
3.	Lead	1. Bluish grey coloured metal. 2. Malleability is very high. 3. Melting Point is 327.4°C. 4. Extrusion is possible in hot condition. 5. Softest and heaviest metal.	1. Paints and pigments are manufactured by lead. 2. Electrical cables find application of lead sheets. 3. In the soldering its used as filler metal.


S.No.	Metals	Properties	Applications
4.	Tin	1. Bright shining coloured metal. 2. Soft and malleable. 3. Melting point is 232°C.	1. With the combination of lead, it is used in soldering process. 2. Moisture proof packings are made of tin. 3. Coating on other metal.
5.	Zinc	1. Bluish-grey coloured metal. 2. Melting point is 481°C.	1. Zinc is used in Brass. 2. Electrical cells. 3. Corrosion resistant coating.
6.	Nickel	1. It is silvery white coloured metal. 2. Melting point is 1452°C. 3. Nickel in the presence of small amount of carbon is malleable. 4. Hard metal.	1. Nickel polishing is done as protective coating. 2. Important alloys are made up with the help of nickel.
7.	Magnesium	1. Melting point is 650°C. 2. It is the lightest metal. 3. Good machinability.	1. Used to manufacture flash light powder.

Introduction to Composites

Definition of Composite: A *Composite* is defined as a material which is a combination of two or more dissimilar materials which have different interfaces between them and the resulting material properties are enhanced compared to the individual constituent materials.

Constituents of a Composite

The main constituents of composites (as in Fig) are the reinforcements and the matrix. In a composite material one material forms a matrix to bond together the other material called *reinforcement material*. The matrix and reinforcement are chosen in such a way that their mechanical properties complement each other, at the same time their deficiencies are neutralised. Example: in Glass Reinforced Plastic moulding, the matrix is the polyester resin and this binds together the glass fiber reinforcement.



Classification of Composites

Composite materials are commonly classified at two distinct levels:

- 1) With respect to *matrix* constituent
 - Polymer matrix composite – matrix is made from a *polymer resin* material
 - Metal matrix composite – matrix is made from a *metal* or *alloy*
 - Ceramic matrix composite – *matrix* is made from a *ceramic material*
- 2) With respect to *reinforced* constituent
 - Fibre reinforced composite – reinforcement is in the form of fiber (thread like structure)
 - Particle (Particulate) reinforced composites – reinforcement is in the form of small particles.
 - Laminated composites – reinforcement consists of layers of material held together.

Metal Matrix Composites (MMC)

Composites are classified as metal matrix composite, when the matrix is made from a metal or alloy. The reinforcement material is usually in the form of fiber, or small sized particles (particulates) made from ceramic or metallic materials.

**** Properties of Metal Matrix Composites***

MMCs offer properties such as higher specific strength, stiffness, higher operating temperature, low co-efficient of thermal expansion and greater wear resistance, and also the opportunity to tailor these properties for a specific application. However, MMCs have lower ductility and the cost of fabricating is high.

Applications of Metal Matrix Composites

1. Used in making piston for diesel engine. The MMC piston offers good wear resistance and strength at high temperatures than compared to the traditional cast iron piston.
2. Metal matrix composites possessing high strength and specific stiffness can be used in applications where weight saving is a vital factor. Examples are robots, high-speed machinery, and high-speed rotating shafts for ships or land vehicles.
3. MMCs are used in automotive engine and brake parts due to its good wear resistance and high specific strength.
4. They are also used in lasers, precision machinery, and electronic packaging due to the tailorable coefficient of thermal expansion and thermal conductivity of the MMC.
5. They also find applications in spacecraft structures, missile structures, fighter aircraft engines and structures.

Fiber Reinforced Composites


Composites are classified as *fiber reinforced composite*, when the **reinforcement** added is in the form of fibers. A fiber is a slender, elongated thread like structure, characterized by length and diameter/thickness. The most common types of fibers used are glass fibers, carbon fibers, and aramid (kevlar) fibers.

Fibers are generally circular in cross-section, but can also be in the form of tubular, rectangle or hexagonal. The diameter of fiber ranges from 0.0001 *inch* to about 0.005 *inch* depending on the material.

Fiber reinforced composites can be further divided based on *discontinuous* or *continuous* type of fibers. Continuous fiber-reinforced composites contain fiber reinforcements having lengths much greater than their cross-sectional dimensions as shown in figure (a). On the other hand, a composite is considered to be a discontinuous fiber or short fiber composite if its properties vary with fiber length as shown in figure (b). Discontinuous fibers can also be randomly

oriented as shown in figure (c). Most practical composites that are being developed for engineering applications contain *discontinuous fibers*.

Most of the fiber reinforced composites contain polymers as matrix material. They are used in the manufacture of doors, windows, bathtubs, boats, yachts, sporting goods, pipes, tanks & vessels, & many internal parts in rail, automotive, and aerospace applications.



Figure

Continuous & discontinuous fibers

ADVANTAGES OF COMPOSITES

1. Higher strength to weight ratio
2. Increased stiffness to density ratio
3. Enhanced fatigue Resistance
4. Better elevated temperature properties
5. Higher strength

6. Lower Creep rate
7. Lower coefficients of thermal expansion
8. Better wear resistance

LIMITATIONS OF COMPOSITES

1. These are more brittle in nature & hence easily damaged.
2. Cost of production is high & Some Composites are difficult to fabricate.
3. Cannot be easily recycled
4. In laminate composites inspection is complicated as there may exists internal defects.

APPLICATIONS OF COMPOSITES IN AUTOMOBILES

MMC are used in

- Suspension system for improved damping & stiffness
- Valves for high temperatures, Creep, wear-resistance.
- Lubrication pump housing for wear resistance & low weight.
- Brake callipers for low wear & weight.
- Drive shaft for high stiffness & fatigue resistance
- Connecting rod for fatigue & wear resistance.
- Car body
- Instrument panel (dash board)
- Bumpers
- Radiators grill
- Automobile sheet metal skin.

APPLICATION OF COMPOSITES IN AIRCRAFTS

- Airframe of an aircraft
- Main landing gear door.
- Nose landing gear door.
- Flap link
- Helicopter Rotor blades
- Aircraft propeller blades
- Aircraft seats
- Instrument panel (dash board)
- Carbon fibre reinforced polymer is used in wing & nose.
- Used to deflect radar waves & also to absorb them.
- Used in fuel tank
- Turbines & combustion chamber Components.

SMART MATERIALS

Smart materials are designed materials having one or more properties that can be significantly changed in a controlled fashion by means of external stimuli, such as stress, temperature, moisture, pH, electric or magnetic fields. The change in properties is reversible and can be repeated any number of times. For example, a particular plastic material which is an *insulator* at normal conditions can be made to behave as a *conductor* by applying a compressive force. Upon removal of the force, the plastic material returns to its insulating state. A photosensitive glass darkens when exposed to sunlight and returns back to its initial state when protected from sunlight. Some materials change colour in response to an electric stimulus. Similarly there are a wide range of materials, each offering different properties under different circumstances. Such materials are designated as *smart materials*, because the response they produce in proportion to a stimulus acts as a *feedback* or a *signal*, allowing decisions to be taken accordingly. For example, an aeroplane might have wings made from a smart material that changes colour as soon as tiny cracks start to develop; a wound dressing that changes its colour when infection develops, & so on. Smart materials have the potential to change technology & design principles completely.

Piezoelectric Materials


Piezoelectric materials are those materials that produce an electric current when they are subjected to mechanical stress. Thus Piezoelectric materials have two unique properties which are interrelated. When a piezoelectric material is deformed by applying stress, it gives off a small electrical discharge. Alternately, when an electrical current is passed through a piezoelectric material it experiences a significant deformation. It is for this property, piezoelectric materials are most widely used as sensors in different environments. Common piezoelectric materials include ceramic materials like Lead zirconium titanate (PZT), Barium titanate, lead zirconate titanate, lead zirconate, potassium niobate, etc., and polymer material like Polyvinylidene fluoride. Typical industrial applications of piezoelectric materials are grouped in table

Sl. No.	Industry	Applications
1.	Automotive	Used as Air bag sensor, air flow sensor, audible alarms, fuel atomizer, keyless door entry, seat belt buzzers, etc.
2.	Computer	Used as actuators for Disc drives, dot-matrix/inkjet printing heads, etc.
3.	Consumer	Used as depth finders, fish finders, humidifiers, jewellery cleaners, musical instruments, speakers found in cell phones and musical greeting cards, telephones. Cigarette lighters etc.
4.	Medical	Used in foetal heart monitors, ultrasonic imaging, ultrasonic cataract removal devices, cochlear implants, etc.
5.	Military	Used in Depth sounders, guidance systems, hydrophones, sonar, etc.
6.	Manufacturing	Used as actuators in ultrasonic cleaning, ultrasonic welding, motors in environments with strong magnetic fields or cryogenic temperatures,

Table Typical industrial applications of piezoelectric materials

Shape Memory Alloys:

- Shape memory alloys are those materials, even after being deformed, have the ability to remember and return to their original shape and size, upon appropriate heat treatment.
- Deformation is normally carried out at relatively low temperature, whereas, shape memory effect happens due to heating.
- Among materials that are capable of recovering significant amounts of deformation, the best known are Nickel-Titanium (NITINOL) alloys; and some Copper based alloys (Cu-Zn-Al and Cu-Al-Ni).



TYPES OF SHAPE MEMORY ALLOY

A variety of alloys exhibit the shape-memory effect. Alloying constituents can be adjusted to control the transformation temperatures of the SMA. Some common systems include the following:

- Cu-Al-Ni
- Cu-Zn
- Fe-Pt
- Mn-Cu
- Fe-Mn-Si
- Ni-Fe-Ga
- Ni-Ti approx. 55–60 wt% Ni
- And Many More....

ADVANTAGES AND DISADVANTAGES OF SHAPE MEMORY ALLOY

Advantages

1. It has higher strain recovery upto 8%.
2. Higher strength of Shape memory alloy is observed.
3. Its High corrosion resistant property make it suitable for use in concrete.
4. It has Good elasticity.
5. It Resist Fatigue .
6. It does not undergo Wear and tear.
7. Easy fabrication of Shape Memory Alloy is possible
8. It is Light in weight.

Disadvantages

1. Heat energy is required to activate
2. The Property Of Shape Memory Alloy.
3. Heat Dissipation - Need Mechanism For Cooling .
4. It Has Less Stiffness.
5. Costly As Compared To Other Materials Such As Steel And Aluminum.
6. It Has Poor Fatigue Properties (I.E. Structural & Functional Fatigue)

Applications of Shape memory alloys

The unusual properties of shape memory alloys have made them a very promising class of metallic materials to be used for a wide variety of applications in a number of different fields. Typical industrial applications of shape memory alloys are grouped in table

Sl. No.	Industry	Applications
1.	Automotive	Automotive thermostats, vibration dampers, cold start vehicle actuators, etc.
2.	Medical	Used in fixed orthodontic treatment for wide dental movements, filter clots that travel inside the bloodstream, healing process of broken and fractured bones, neuromuscular rehabilitation like spastic limb repositioning, or residual voluntary movement of neurological members, Arterial clips, key-hole surgery instruments, etc.
3.	Aircraft	Used in vibration dampers to dissipate energy and dampen vibrations for launch vehicles and commercial jet engines; as actuators in jet engines to reduce weight and boost efficiency; in ball bearings and landing gear for shock applications, etc.
4.	Others	Used in robot actuators to mimic the smooth movement of human muscles, solar actuators, electrical circuit breakers, fiber optic coupling, mobile phone antennas, satellite antenna deployment, spectacle frames, Intraocular lens mount, structural applications susceptible to seismic activity, column-foundation bolted joints, slender structures for control of buckling and vibrations, etc.

Table Typical industrial applications of shape memory alloys

MR Fluids

Magnetorheological (MR) fluid is a "smart" material composed of micron-sized magnetic particles (usually iron) suspended in a carrier oil, which changes from a liquid to a near-solid state within milliseconds when exposed to a magnetic field. This reversible, controllable, and rapid viscosity change allows it to be used for precise force control in vehicle dampers, automotive clutches, seismic dampers, and prosthetic limbs.

Key Aspects of MR Fluid:

Mechanism: Without a magnetic field, the fluid flows freely. When a magnetic field is applied, the iron particles align into chains, causing the fluid to behave like a visco-elastic solid.

Composition: Primarily consists of soft magnetic particles, a carrier fluid (like oil), and surfactants to prevent sedimentation

Key Properties

- Fast response time (milliseconds)
- Controllable viscosity
- Reversible behaviour
- Operates over wide temperature range
- High yield stress under magnetic field

Applications:

- **Automotive:** Suspensions, shock absorbers, and engine mounts.
- **Industrial:** Clutches, brakes, and polishing tools.
- **Structural:** Seismic dampers for buildings.

Introduction to Nano-materials:

Nanomaterials are materials that have at least one dimension in the nanometer range, typically between 1 and 100 nanometers. This size range is crucial because it imparts unique physical, chemical, and biological properties to the materials that are not observed in their bulk counterparts. At the nanoscale, materials exhibit increased surface area to volume ratios, quantum effects, and other phenomena that can significantly alter their behavior and interactions.

Nanometer scale

Nanoscale is an extremely small scale where objects in the range of 1–100 nm are taken into consideration. For something to officially be a nanomaterial, at least one of its dimensions must be smaller than 100 nm.

Classification of Nanomaterials:

Nanomaterials can be broadly classified into several categories based on their dimensions:


1. **Zero-Dimensional (0D) Nanomaterials:** These are materials where all three dimensions are in the nanoscale. Examples include nanoparticles, nanospheres, and nanoclusters. They are often used in biomedical applications, including drug delivery and imaging, due to their small size and high surface area.
2. **One-Dimensional (1D) Nanomaterials:** These materials have one dimension outside the nanoscale. Examples include nanowires, nanotubes, and nanorods. One-dimensional nanomaterials are used in electronics and photonics for their ability to conduct electricity and light efficiently along their length.
3. **Two-Dimensional (2D) Nanomaterials:** These materials have two dimensions outside the nanoscale. Examples include graphene, nanofilms, and nanocoatings. Two-dimensional nanomaterials are known for their excellent mechanical, electrical, and thermal properties and are used in applications ranging from flexible electronics to barrier coatings.
4. **Three-Dimensional (3D) Nanomaterials:** These materials have three dimensions outside the nanoscale but contain nanoscale features, such as nanocomposites and nanostructured bulk materials. Three-dimensional nanomaterials combine the properties of their nanoscale components with those of bulk materials, making them suitable for structural applications and advanced material design.

Types of Nanomaterials

There are four types of nanomaterials. They are:

- **Nanoparticles:** Nanoparticles are particles that have a measurement of less than 100 nanometres in at least one dimension.
- **Nanofibers:** Nanofibers are long, thin fibers with sizes in the nanometre range.
- **Nanotubes:** Nanotubes are tubes with walls composed of only one layer of atoms and diameters within the nanoscale range.
- **Nanolaminates:** These are composite materials made of thin layers of various materials layered on top of one another.

Applications of Nanomaterials



Nanomaterials may be used technologically in a variety of fields, including air purification, environmental preservation, and the medical and mechanical fields. They may be used for the development of stronger, lighter materials, more effective medicine delivery systems, and batteries that are more efficient. The following are the applications of nanomaterials:

Electronics: Nanomaterials have the potential to enhance the efficacy and reduce the power consumption of electronic devices such as smartphones, computers, and televisions. Other objectives include the development of high-resolution displays and the enhancement of the efficacy and storage capacity of rechargeable batteries.

Medicine: It may be employed for treatment, diagnosis, and imaging, among other medical applications. Nanoscale medication delivery systems may improve target specificity and efficacy.

Environmental remediation: The process of removing pollutants and contaminants from contaminated air, soil, and water through the use of nanofilters and catalysts that are based on nanoparticles. These nanofilters are also capable of eliminating pathogens.

Materials science: Materials science has the potential to generate materials that are more durable, lightweight, and possess superior thermodynamic and mechanical properties. Subsequently, they may be implemented in aerospace and automotive components or other demanding applications.

Food and agriculture: To enhance the quality, safety, and shelf life of food or agricultural goods by increasing the efficiency and effectiveness of pesticides while reducing their environmental impact, as well as the efficiency and effectiveness of irrigation systems. This will result in improved crop growth and reduced water consumption.

Advantages and Disadvantages of Nanomaterials

Advantages

1. **High Strength and Lightweight**
Nanomaterials such as Carbon Nanotubes are extremely strong yet very light, making them useful in aerospace, automobiles, and sports equipment.
2. **Improved Electrical Conductivity**
Materials like Graphene conduct electricity better than many traditional materials, improving electronic devices and batteries.
3. **Large Surface Area**
Nanomaterials have a very high surface area compared to their volume, increasing their chemical reactivity. This is useful in catalysts and sensors.
4. **Medical Applications**
Used in drug delivery systems, cancer treatment, imaging, and diagnostics with better precision and fewer side effects.
5. **Better Energy Efficiency**
Improve performance of solar cells, fuel cells, and energy storage devices.
6. **Environmental Applications**
Help in water purification, air filtration, and pollution control.

Disadvantages

1. **Health Risks**
Some nanoparticles may cause respiratory problems or cell damage if inhaled or absorbed.
2. **Environmental Impact**
Nanoparticles can accumulate in soil and water, potentially harming ecosystems.
3. **High Production Cost**
Manufacturing requires advanced technology and is often expensive.
4. **Toxicity Issues**
Certain nanomaterials may be toxic to humans and animals.
5. **Lack of Regulations**
Safety guidelines and regulations are still developing in many countries.
6. **Difficult Disposal**
Recycling and safe disposal methods are not yet fully developed.